



DEWATERING FILTRATION BAG SIZE	MAXIMUM GALLON PER MINUTE CAPACITY
4' x 6'	228
7.5' x 7.5'	534
10' x 10'	950
10' x 15'	1,425
15' x 15'	2,137
15' x 30'	4,275
15' x 65'	9,262

INSTALLATION AND MAINTENANCE GUIDELINES

INSTALLATION: PLACE LIFTING STRAPS (NOT INCLUDED) UNDER THE UNIT TO FACILITATE REMOVAL AFTER USE. UNFOLD D2 DEWATERING BAG ON A STABILIZED AREA OVER DENSE VEGETATION, STRAW OR OTHER COVER. PLACE BAG OVER OPEN GRADED STONE TO ACHIEVE MAXIMUM FILTRATION AND DRAINAGE. INSERT DISCHARGE HOSE FROM PUMP INTO D2 DEWATERING BAG A MINIMUM OF SIX INCHES AND TIGHTLY SECURE WITH STAINLESS STEEL WORM GEAR CLAMP TO PREVENT WATER FROM FLOWING OUT OF THE UNIT WITHOUT BEING FILTERED. MAINTENANCE: REPLACE THE UNIT WHEN ½ FULL OF SEDIMENT OR WHEN SEDIMENT HAS REDUCED THE FLOW RATE OF THE PUMP DISCHARGE TO AN IMPRACTICAL RATE.

*DISCLAIMER:
D2 LAND & WATER RESOURCE, INC. ASSUMES NO RESPONSIBILITY FOR THE DRAWINGS AND CALCULATIONS IT PROVIDES, AS THEY MUST BE INTENDED AS A GENERAL INDICATION TO SUGGEST THE PROPER USE OF ITS PRODUCTS



A PRODUCT OF:
D2 LAND & WATER RESOURCE, INC.
 2600 BLOYD AVE. PH: (800) 597-2180
 INDIANAPOLIS, IN 46218 FAX: (317) 917-2181

DESCRIPTION:
 NON-WOVEN DEWATERING BAG STANDARD DETAIL AND SIZING CHART

CLIENT:

DATE ISSUED: 08/26/16	DRAWN BY: JAR	CHK'D BY: JAB	SCALE: N.T.S.
--------------------------	------------------	------------------	------------------

DRAWING NAME:

D2 DEWATERING BAG
 DETAIL A01