

REINFORCED CORNERS
SEWN ON FABRIC PIECE
2" DOWN FROM TOP SEAM
(5" WIDE X 7" TALL)
(2 PER SIDE, 4 TOTAL)

REINFORCED OVERFLOW
(STITCHING AROUND PERIMETER
OF OVERFLOW HOLE)

3" X 12" OVERFLOWS
6" DOWN FROM TOP SEAM
(1 PER LENGTH, 2 TOTAL)

ECONOSACK TO BE PRODUCED
USING HIGH FLOW, HIGH VISIBILITY
YELLOW WOVEN FABRIC

DUMPING STRAPS
(TYP. PER 2)

LIFT STRAPS
(TYP. PER 2)

9"

NOTES:

- 1) TYPICAL ECONOSACK HEIGHT/DEPTH IS 24"
- 2) ECONOSACK TO BE PRODUCED USING HIGH FLOW, HIGH VISIBILITY WOVEN FABRIC

ACF ECONOSACK WITH OVERFLOWS

FERGUSON
WATERWORKS

CORPORATE OFFICE
2831 CARDWELL RD
RICHMOND, VA 23234
INFOGEO@FERGUSON.COM
WWW.FERGUSONGSS.COM

FOR ADDITIONAL INFORMATION PLEASE
CONTACT FERGUSON SALES
INFOGEO@FERGUSON.COM OR VISIT
WWW.FERGUSONGSS.COM