



General Product Specification

| | |
|-----------------|---------|
| Item No. | GPSK-PP |
|-----------------|---------|

| | |
|-------------|-----------|
| Date | 6/12/2016 |
|-------------|-----------|

| | |
|------------------|---|
| No. Pages | 1 |
|------------------|---|

Product Description:

| | |
|-------------------------|--|
| Style | Universal Spill Kit |
| Item Size (each) | N/A |
| Color | N/A |
| Composition | 100% Polypropylene |
| Structure | Contains: 2- 3" x 4' socks, 10- 15" x 18" pads, 1- disposal bags with ties, 1- pair nitrile gloves, 1- instruction sheet, packaged in a yellow economy bag |
| Technology | Meltblown |
| Absorbency | Universal (Hydrophilic) |
| Bonding | N/A |

| | |
|-----------------------------|-----------------------------------|
| Intended Application | Universal (Hydrophilic) absorbent |
|-----------------------------|-----------------------------------|

| | |
|----------------------------|----------------------|
| Absorbency Capacity | 5.0 gallons per bale |
|----------------------------|----------------------|

Packaging Description:

| | |
|--------------------------------|-------------------------|
| Packaging Configuration | case |
| Items Per Package | 1 Spill Kit/case |
| Container Type | Vinyl Zipper Case |

| | |
|---------------------------|---------|
| Package Weight | 4.8 lbs |
| Package Dimensions | N/A |

Physical Properties:

| Parameter | MBT Test Method | Units | Nominal | (+/-) Tolerance |
|------------------------|-----------------|-------|---------|-----------------|
| Basis Weight | MBTTM001 | LBS | 4.8 | 2 |
| Absorbency** (med Oil) | MBTTM012 | GAL | 5.0 | 7 |
| 3" Tensile Strength | MBTTM02 | LBS | N/A | N/A |
| Color | N/A | | | |

The above properties are "nominal" values used for process control when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or environment being applied, stored, or shipped.

** The "Absorbency" spec and "MBTTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

| | |
|----------------------|--|
| Attributes | Product will be free of foreign material contamination, rips, holes and tears. |
| Labeling | |
| Certification | Make no changes in basic process or composition without notifying customer. |